

CP2500-E

便携式储能电源

昆宇电源
COSPOWERS



型号		CP2500-E
基本参数	容量	2560Wh
	净重	32kg
	尺寸 (L*W*H)	514*258*357(mm)
	App	Wi-Fi
输出	交流输出	10A五孔插座*2个; 16A三孔插座*1个, 3600W(额定功率); 3960W < P ≤ 4680W, 30s后锁死; 4680W < P ≤ 6000W, 2s后锁死; P > 7200W, 200ms后锁死;
	USB-A	1路输出, 5V/2.4A(恒压), 最大功率12W/路
	USB-A快充	1路输出, 5V/2.4A, 9V/2A, 12V/1.5A(恒压), 最大功率18W/路
	USB-C	2路输出, 5/9/12/15/20V--5A(恒压), 最大功率100W/路, 支持PD3.0
	车充输出	12V/10A, 最大功率120W
	DC5521输出	12V/3A 2路, 最大功率36W/路
	无线充电	支持, 15W
	安德森端口	支持, 12V/30A
输入	交流输入功率	2200W
	交流输入电压	AC220 10A 50Hz
	太阳能充电输入	800W
	车充输入	支持12/24V电池
电池	电芯	LFP/半固态电池
	循环寿命	3500次循环后剩余容量仍有80%以上
	保护类型	高温保护、低温保护、过放保护、过充保护、过载保护、短路保护、过流保护
温度	放电环境温度	-20°C~45°C
	充电环境温度	0°C~45°C
	存储环境温度	0°C~45°C
	锂电池加电包	支持
其他	手电筒	户外照明及紧急呼救
	收纳盒	数据线套装
	主动灭火装置	支持



深圳昆宇电源科技有限公司

网址: WWW.COSPOWERS.COM

地址: 深圳市宝安区燕罗街道罗田社区第三工业区广田路2号

电话: 0755-33185898

版权及最终解释权归深圳昆宇电源科技有限公司所有

CP2500-E

COSPOWERS

PORTABLE ENERGY STORAGE POWER SUPPLY



Model		CP2500-E
Basic parameters	Capacity	2560Wh
	Net weight	32kg
	Size (L*W*H)	514*258*357(mm)
	App	Wi-Fi
Output	AC output	10A five-hole socket*2; 16A three-hole socket*1; 3600W (rated power)
		3960W < P ≤ 4680W, It locks up after 30s
		4680W < P ≤ 6000W, It locks up after 2 seconds
		P > 7200W, It locks up after 200ms
	USB-A	1 channel output, 5V/2.4A constant voltage, max power 12W/channel
	USB-A fast charge	1 channel output, 5V/2.4A, 9V/2A, 12V/1.5A(constant voltage), max power 18W/channel
	USB-C	2 channels output, 5/9/12/15/20V--5A(constant voltage), max power 100W/channel, supporting PD3.0
	Car charge output	12V/10A, max power 120W
	DC5521Output	12V/3A 2 channels, max power 36W/channel
	Wireless charge	Available, 15W
Anderson port	Available, 12V/30A	
Input	AC Input Power	2200W
	AC Input Voltage	AC220 10A 50Hz
	Solar Charge Input	800W
	Vehicle charger Input	Support 12/24V battery
Battery	Cell	LFP/semi-solid battery
	Life cycles	After 3500 cycles, the remaining capacity is still more than 80%
	Protection type	High temperature protection, low temperature protection, over discharge protection, over charge protection, overload protection, short circuit protection
Temperature	Discharge Temperature	-20°C~45°C
	Charge Temperature	0°C~45°C
	Storage Temperature	0°C~45°C
	Li-ion battery with power pack	Available
Others	Torch	Outdoor lighting and emergency calls
	Storage box	Data cable set
	Active extinguishing Device	Available



Shenzhen Coslight Power Technology Co., Ltd.

W: WWW.COSPOWERS.COM

A: No.2, Guangtian Road, No.3 Industrial Zone, Luotian Community, Yanluo Street, Baoan District, Shenzhen, Guangdong Province, P.R.C

T: +86-755-33185898

Copyright and final interpretation rights belong to Shenzhen Coslight Power Technology Co., Ltd.