

# CE-5 低压壁挂式储能电池

昆宇电源  
COSPOWERS



- 1 外观极简设计，优雅美观
- 2 防护等级IP40
- 3 支持多电池模组并联，最多可支持8个模块
- 4 简易安装和维护，满足不同客户定制化设计
- 5 多重保护及告警系统，安全可靠

| 参数 / 型号 |           | CE-5   |
|---------|-----------|--|
| 电池参数    | 额定电压      | 51.2V  |
|         | 电压范围      | 45~57.6V   |
|         | 电量        | 5120Wh   |
|         | 标准充放电电流   | 0.25C/0.5C   |
|         | 最大充放电电流   | 0.5C/1C  |
| 工作条件    | 电池类型      | 磷酸铁锂   |
|         | 工作温度范围    | 0~45°C   |
|         | 存储温度范围    | -15°C~60°C   |
|         | 湿度        | 5%~95%   |
|         | 冷却方式      | 自然冷却   |
|         | 重量        | 46kg   |
|         | 尺寸(W*D*H) | 430*186*600mm  |
| 其他      | 防护等级      | IP20   |
|         | 安装方式      | 壁挂式  |
|         | 通讯方式      | RS485/WIFI (选配)  |
|         | 匹配逆变器     | 派能、古瑞瓦特、硕日、固德威、锦浪、鹏城、日月源、Victron、索瑞德、施耐德、SMA、美世乐、拓宝、STUDER |



深圳昆宇电源科技有限公司

网址: WWW.COSPOWERS.COM

地址: 深圳市宝安区燕罗街道罗田社区第三工业区广田路2号

电话: 0755-33185898

版权及最终解释权归深圳昆宇电源科技有限公司所有

# CE-5

## WALL HANGING ENERGY STORAGE POWER SUPPLY



- 1 Extreme simple appearance design, elegant and beautiful
- 2 Protection class IP40
- 3 It supports multiple battery modules in parallel, up to 8 modules
- 4 Easy installation and maintenance, customized design to meet the requirements of different customers
- 5 Multiple protection and alarm system, safe and reliable

| Parameters/ Model  |                                   | CE-5   |
|--------------------|-----------------------------------|--|
| Battery Parameters | Rated voltage                     | 51.2V  |
|                    | Voltage range                     | 45~57.6V   |
|                    | Energy                            | 5120Wh   |
|                    | Standard Charge/Discharge Current | 0.25C/0.5C   |
|                    | Max. Charge/Discharge Current     | 0.5C/1C  |
| Working Conditions | Battery Type                      | LFP  |
|                    | Operating temperature range       | 0~45°C   |
|                    | Storage temperature range         | -15°C~60°C   |
|                    | Humidity                          | 5%~95%   |
|                    | Cooling Method                    | Natural cooling  |
|                    | Weight                            | 46kg   |
|                    | Size                              | 430*186*600mm  |
|                    | IP Class                          | IP20   |
| Others             | Installation method               | Wall mounting type   |
|                    | Communication port                | RS485/WIFI (Optional)  |
|                    | Integrated Inverters              | Pylon, Growatt, SRNE Solar, Goodwe, Ginlong, Pengcheng, Riyueyuan, Victron, Sorotek, Schneider, SMA, Meishile, TBB, Studer |



Shenzhen Coslight Power Technology Co., Ltd.

W: WWW.COSPOWERS.COM

A: No.2, Guangtian Road, No.3 Industrial Zone, Luotian Community, Yanluo Street, Baoan District, Shenzhen, Guangdong Province, P.R.C

T: +86-755-33185898

Copyright and final interpretation rights belong to Shenzhen Coslight Power Technology Co., Ltd.