

# PowerEco-200kW/372kWh

# PowerEco-200kW/417kWh



灵活扩容, 一机多效  
匹配多种应用场景



多重  
保护系统



高集成化设计  
交直流一体



指尖监控  
云端维护

参数 / 型号		PowerEco-200kW/372kWh	PowerEco-200kW/417kWh
直流侧参数	直流路数	1路	
	直流母线最高电压	1500V	
	直流侧最大电流	189A	
	直流电压工作范围	1060~1500V	
交流侧参数	最大输入视在功率	220kVA	
	最大输入有功功率	200kW	
	额定输入电压	690V	
	最大持续输入电流	184A	
	额定输入频率	50/60Hz	
电池参数	电池类型	磷酸铁锂	
	额定电量	372kWh	417kWh
	标称电压	1331.2V	
	工作电压范围	1164.8~1456V	
	倍率	≤0.5C	
系统参数	人机界面	8寸 LCD触摸屏	
	消防系统	全氟己酮消防	
	冷却方式	液冷	
	工作温度	0~55°C	
	防护等级	IP54	
	尺寸(W*D*H)	<1400*1400*2350mm	
	重量	<3000Kg	



昆宇电源股份有限公司

网址: WWW.COSPOWERS.COM

地址: 山东省东营市东营区东七路28号

电话: 0546-7768891

版权及最终解释权归昆宇电源股份有限公司所有

# PowerEco-200kW/372kWh

# PowerEco-200kW/417kWh



flexible expansion, one machine multi-effect matching a variety of application scenarios



Multiple Protection Systems



highly integrated design AC and DC integrated



fingertip monitoring cloud maintenance

Parameters/ Model		PowerEco-200kW/372kWh	PowerEco-200kW/417kWh
直流侧参数	DC branch	1 channel	
	DC busbar maximum voltage	1500V	
	DC side maximum current	189A	
	DC voltage operating range	1060~1500V	
交流侧参数	Maximum input apparent power	220kVA	
	Maximum input active power	200kW	
	Rated input voltage	690V	
	Maximum continuous input current	184A	
	Rated input frequency	50/60Hz	
电池参数	Battery Type	LFP	
	Rated capacity	372kWh	417kWh
	Nominal voltage	1331.2V	
	Operating voltage range	1164.8~1456V	
	Charge/Discharge Rate	≤0.5C	
系统参数	HMI	8 inch LCD touch screen	
	Fire protection system	Perfluorhexone fire protection	
	Cooling Method	Liquid cooling	
	Operating temperature	0~55°C	
	IP Class	IP54	
	Size (W*D*H)	<1400*1400*2350mm	
	Weight	<3000Kg	



Cospowers Technology Co., Ltd.  
 W: WWW.COSPOWERS.COM  
 A: No.28, Dongqi Road, Dongying City, Shandong Province, P.R.C.  
 T: +86-546-7768891  
 Copyright and final interpretation rights belong to Cospowers Technology Co., Ltd.