

Celestial Energy-2073-0.5C

COSPOWERS

Application Field

- Post-meter electricity market, peak-valley arbitrage and backup power supply of C&I (commercial and industrial) energy storage on the customer side.
- Peak shaving and valley filling for smooth output of wind and solar new energy power stations.
- Grid frequency regulation and peak load regulation in the pre-meter electricity market, as well as capacity expansion of distribution network transformers.



Modular Standard Design



Multiple Protection Systems



Efficient Installation and Commissioning of AC/DC Integrated Systems



Intelligent Operation and Maintenance

Parameters/ Model		Celestial Energy-2073-0.5C
DC side parameters	Cell Capacity	100Ah
	Module Structure	3P18S
	Module quantity in single cluster	20pcs
	Nos. of Battery Clusters	6pcs
	Battery system power	2073kWh
	Voltage Range	1008~1278V
AC side parameters	Rated grid voltage	6*200kW
	Wiring Mode	690V
	Rated grid frequency	3W+PE
	Rated AC power	50/60Hz
	Isolation mode	No isolation transformer
System level parameters	Operating temperature	-30~55°C
	Ambient Humidity	0~95% (no condensation)
	Working Altitude	2000m
	Communication method	Ethernet, RS485, Optional 4G/5G Mobile Communication
	Protection level	IP54
	Cooling Method	Air cooling
	Noise	≤65dB
	Fire protection system	Heptafluoropropane/Perfluorohexanone compartment level/Aerosol ten water fire protection + combustible gas detection + explosion-proof ventilation system
	Size(W*D*H)	6058*2438*2896mm
	Weight	24t
Compliant with Standards	Cluster	IEC62619, UL1973, UL9540A, UN38.3
	PCS	UL1741, EN50549, VDE4110, GB/T34120, GB/T36547



Cospowers Technology Co., Ltd.

W: WWW.COSPOWERS.COM

A: No.28, Dongqi Road, Dongying City, Shandong Province, P.R.C.

T: +86-546-7768891

Copyright and final interpretation rights belong to Cospowers Technology Co., Ltd.