

EnerGalactic-2980-1C

COSPOWERS

Application Field

- Post-meter electricity market, peak-valley arbitrage and backup power supply of C&I (commercial and industrial) energy storage on the customer side.
- Peak shaving and valley filling for smooth output of wind and solar new energy power stations.
- Grid frequency regulation and peak load regulation in the pre-meter electricity market, as well as capacity expansion of distribution network transformers.



Temperature Difference
inside the Battery
Pack: <math>< 5^{\circ}\text{C}</math>



Triple-level Fire
Protection for
High Safety



High Energy Density
for Flexible Layout
and Expansion



Modular Prefabrication
No On-site Installation
Required

Parameters/ Model		EnerGalactic-2980-1C
Battery module	Cell Capacity	280Ah
	Battery Pack	1P52S
	Module Voltage	166.4V
	Module Power	46.59kWh
	IP Class	IP67
Battery cluster	NOs.of Modules	8pcs
	Cluster Nominal Voltage	1331.2V
	Voltage Range	1164.8~1476.8V
	Single Cluster Power	372.73kWh
Battery cabin	Nos. of Battery Clusters	8pcs
	Battery system energy	2981kWh
	Battery Cabin Dimension (W*D*H)	6058*2438*2896mm
	Weight	≤33t
	Cooling Method	Liquid cooling
	IP Class	IP54
Compliant with Standards	Cluster	IEC62619, UL1973, UL9540A, UN38.3



Cospowers Technology Co., Ltd.

W: WWW.COSPOWERS.COM

A: No.28, Dongqi Road, Dongying City, Shandong Province, P.R.C.

T: +86-546-7768891

Copyright and final interpretation rights belong to Cospowers Technology Co., Ltd.