

PowerEco-100kW/232kWh

COSPOWERS

Application Field

Commercial Building, Industrial Park,
Industrial Estate



flexible expansion, one machine
multi-effect matching a variety
of application scenarios



Multiple Protection
Systems



highly integrated
design AC and DC
integrated



fingertip monitoring
cloud maintenance

Parameters/ Model		PowerEco-100kW/232kWh
DC side parameter	Max Voltage	950V
	Max Current	170A
	Voltage Range	650~950V
	Max. Apparent Output	115.5kVA
AC grid connection parameter	Max. Input Active Power	105kW
	Nominal Voltage	400Vac, 3P3W+PE/3P4W+PE
	Max. Input Current	167A
	Nominal Input Frequency	50/60Hz
AC off-grid parameter	Nominal Voltage	400Vac, 3P3W+PE/3P4W+PE
	Max Output Current	167A
	Nominal Frequency	50/60Hz
Battery parameters	Battery Chemistry	LFP
	Capacity	232kWh
	Nominal Voltage	832V
	Voltage Range	728~910V
	C Rate	≤0.5C
System level parameters	HMI	7 Inch touch screen
	Fire Safety	Perfluorohexane fire protection/Aerosol
	Cooling Method	Liquid Cooling
	Operating Temp.	-20~55°C
	IP Degree	IP54
	Dimension(W*D*H)	<1100*1350*2350mm
Others	Weight	<2800Kg
	Certification	Domestic Type Test Report



Cospowers Technology Co., Ltd.

W: WWW.COSPOWERS.COM

A: No.28, Dongqi Road, Dongying City, Shandong Province, P.R.C.

T: +86-546-7768891

Copyright and final interpretation rights belong to Cospowers Technology Co., Ltd.