

PowerEco-250kW/464kWh

Application Field

Commercial Building, Industrial Park,
Large Industrial Park



flexible expansion, one machine multi-effect matching a variety of application scenarios



Multiple Protection Systems



highly integrated design AC and DC integrated



fingertip monitoring cloud maintenance

Parameters/ Model		PowerEco-250kW/464kWh	PowerEco-250kW/522kWh
DC side parameter	Max Voltage	950V	
	Max Current	340A	406A
	Voltage Range	650~950V	
	Max. Apparent Output	275kW	
AC grid connection parameter	Max. Input Active Power	250kW	
	Nominal Voltage	400Vac, 3P3W+PE/3P4W+PE	
	Max. Input Current	400A	
	Nominal Input Frequency	50/60Hz	
AC off-grid parameter	Nominal Voltage	400V, 3P3W+PE/3P4W+PE	
	Max Output Current	416A	
	Nominal Frequency	50/60Hz	
Battery parameters	Battery Chemistry	LFP	
	Capacity	464kWh	522kWh
	Nominal Voltage	832V	
	Voltage Range	728~910V	
System level parameters	C Rate	≤0.5C	
	HMI	7 Inch touch screen	
	Fire Safety	Perfluorohexane fire protection/Aerosol	
	Cooling Method	Liquid Cooling	
	Operating Temp.	-20~55°C	
	IP Degree	IP54	
Others	Dimension(W*D*H)	2400*1400*2300mm	
	Weight	<4500Kg	<4600Kg
	MPPT	50KW*4 (Optional)	
	STS	/	
	Certification	Undergoing Certification	



Cospowers Technology Co., Ltd.

W: WWW.COSPOWERS.COM

A: No.28, Dongqi Road, Dongying City, Shandong Province, P.R.C.

T: +86-546-7768891

Copyright and final interpretation rights belong to Cospowers Technology Co., Ltd.