

PowerCrate-CE-5 PowerCrate-CE-15

LOW VOLTAGE WALL HANGING TYPE-ENERGY STORAGE BATTERY



- 1 Extremely simple design in appearance, elegant appearance, IP40
- 2 It supports multiple battery modules in parallel, up to 8 modules
- 3 Multiple protection and alarm system, safe and reliable
- 4 Easy installation and maintenance, customized design to meet the requirements of different customers

Parameters/ Model		CE-5	CE-15
Battery Parameters	Rated voltage	51.2V	
	Voltage range	45~57.6V	44.8~57.6V
	Energy	5120Wh	14340Wh
	Max discharge rate	1C	0.5/1C
	Type of battery	LFP	
Operating condition	Operating temperature range	0~45°C	
	Storage temperature range	-15~60°C	-15~30°C
	Humidity	5~95%	
	Dissipation method	Natural cooling	
	Weight	53Kg	112Kg
	Size (W*D*H)	430*186*600mm	413*233*825mm
	Installation method	Wall-mounted	Portable floor-standing
	Communication method	CAN/RS485	
Others	Matched inverter	Pylontech, Growatt, Shorun, Goodwe, Jinlang, Pengcheng, RYR, Victron, Sorou, Schneider, SMA, MSL, Topower, STUDER	Pylontech, Growatt, Shorun, GoodWe, Pengcheng, Maiden Voyage, RYR, Victron, Sorou, Schneider, SMA, MSL, Topower, STUDER
	Certification	IEC62619, CE-EMC, FCC, UL1973, UL9540A	



Shenzhen Coslight Power Technology Co., Ltd.

W: WWW.COSPOWERS.COM

A: No.2, Guangtian Road, No.3 Industrial Zone, Luotian Community, Yanluo Street, Baoan District, Shenzhen, Guangdong Province, P.R.C

T: +86-755-33185898

Copyright and final interpretation rights belong to Shenzhen Coslight Power Technology Co., Ltd.