COSPOWERS

PowerEco-372kWh PowerEco-417kWh

Application Field Commercial Building, Industrial Park, Industrial Estate





flexible expansion, one machine multi-effect matching a variety of application scenarios



Multiple Protection Systems



highly integrated design



fingertip monitoring cloud maintenance

	Parameters/ Model	PowerEco-372kWh	PowerEco-417kWh
Battery parameters	Cell Capacity	280Ah (LFP)	314Ah (LFP)
	Nominal Capacity	372kWh	417kWh
	Nominal Voltage	1331.2V	
	Operating Voltage Range	1164.8~1456V	
	C Rate	7 Inch touch screen	
	HMI	≤0.5C	
System level parameters	Fire Protection	Perfluoroketone Firefighting	
	Cooling Method	Liquid Cooling	
	Humidity	5~95%,RH	
	Working Temp.	-10~55°C	
	IP Class	IP54	
	Dimension	<1400*1400*2350mm	
	Weight	3500Kg	3600Kg
Others	Certification	Undergoing Certification	



Cospowers Technology Co., Ltd.

W:WWW.COSPOWERS.COM

A: No.28, Dongqi Road, Dongying City, Shandong Province, P.R.C.

T:+86-546-776889

Copyright and final interpretation rights belong to Cospowers Technology Co., Ltd.