
EnerGalactic-5015-0.5C



Application Field

- Post-meter electricity market, peak-valley arbitrage and backup power supply of C&I (commercial and industrial) energy storage on the customer side.
- Peak shaving and valley filling for smooth output of wind and solar new energy power stations.
- Grid frequency regulation and peak load regulation in the pre-meter electricity market, as well as capacity expansion of distribution networktransformers.





Temperature Difference inside the Battery Pack: <3°C



High Safety Fire Protection at the Pack Level



High Energy Density for Flexible Layout and Expansion



Modular Prefabrication No On-site Installation Required

Parameters/ Model		EnerGalactic-5015-0.5C	
Battery Module	Cell Capacity	314Ah (LFP)	
	Battery Pack	1P52S	1P104S
	Module Voltage	166.4V	332.8V
	Module Power	52.2496kWh	104.499kWh
	IP Class	IP67	
Battery Cluster	NOs.of Modules	8pcs	4pcs
	Cluster Nominal Voltage	DC1331.2V	
	Voltage Range	1164.8~1476.8V	
	Single Cluster Power	417.997kWh	
Battery Cabin	Nos. of Battery Clusters	12pcs	
	Battery system energy	5015kWh	
	Battery Cabin Dimension(W*D*H)	6058*2438*2896mm	
	Weight	≤43t	
	Cooling Method	Liquid Cooling	
	IP Class	IP54	
Compliant with Standards	Cluster	IEC62619、UL1973、UL9540A、UN38.3	



Cospowers Technology Co., Ltd.

W:WWW.COSPOWERS.COM

A: No.28, Dongqi Road, Dongying City, Shandong Province, P.R.C.

T:+86-546-7768891

Copyright and final interpretation rights belong to Cospowers Technology Co., Ltd.