

EnerGalactic-3727-1C

COSPOWERS

Application Field:

- Peak-valley arbitrage and backup power for customer-side C&I commercial and industrial energy storage;
- Peak shaving, valley filling, and output smoothing for renewable energy stations (wind and solar);
- Grid-side frequency regulation, peak shaving, and distribution network transformer capacity expansion.



Temperature difference across the entire cabinet < 5°C



Three-tier fire protection, high safety



High energy density, flexible layout and scalability



Modular prefabrication, no on-site installation required

Parameters/ Model		EnerGalactic-3727-1C
Battery Module	Cell Capacity	280Ah-LFP
	Module Configuration	1P52S
	Module Nominal Voltage	166.4V
	Module Energy	46.59kWh
	Protection Level	IP67
Battery Rack	Number of Modules	8pcs
	Battery Rack Nominal Voltage	DC1331.2V
	Voltage Range	1164.8~1476.8V
	Single Rack Energy	372.73kWh
Battery Enclosure	Number of Battery Racks	10pcs
	Battery System Energy	3727kWh
	Dimensions (W*D*H)	6058*2438*2896mm
	Weight	≤39t
	Cooling Method	Liquid Cooling
	Protection Level	IP54
Other Parameters	Compliance Standards	IEC62619、UL1973、UL9540A、UN38.3



Cospowers Technology Co., Ltd.

W: WWW.COSPOWERS.COM

A: No.28, Dongqi Road, Dongying City, Shandong Province, P.R.C.

T: +86-546-7768891

Copyright and final interpretation rights belong to Cospowers Technology Co., Ltd.