

Low-voltage wall-mounted energy storage battery



- 1 Extremely simple design in appearance, elegant appearance, IP40
- 2 It supports multiple battery modules in parallel, up to 8 modules
- 3 Multiple protection and alarm system, safe and reliable
- 4 Easy installation and maintenance, customized design to meet the requirements of different customers

Parameters/ Model		CE-5
Battery Parameters	Rated Voltage	48V
	Voltage Range	44.8~57.6V
	Battery Capacity	5120Wh
	Maximum Charge/Discharge Current	0.5C/0.5C
	Battery Type	LFP
Operating Conditions	Operating Temperature Range	0~45°C
	Storage Temperature Range	-15~30°C
	Humidity	5~95%
	Cooling Method	Natural Cooling
	Weight	53Kg
	Dimensions (W*D*H)	430*186*600mm
	Installation Method	Wall-Mounted
	Communication Interface	CAN/RS485
Other Parameters	Compatible Inverter	Pylontech, Growatt, Solis, Goodwe, Ginlong, Prowatt, Sinoyaz, Victron, SuoRuid, Schneider, SMA, Maruson, Topbatt, STUDER
	Certifications	IEC62619、CE-EMC、FCC、UL1973、UL9540A



Shenzhen Coslight Power Technology Co., Ltd.

W: WWW.COSPOWERS.COM

A: No.2, Guangtian Road, No.3 Industrial Zone, Luotian Community, Yanluo Street, Baoan District, Shenzhen, Guangdong Province, P.R.C

T: +86-755-33185898

Copyright and final interpretation rights belong to Shenzhen Coslight Power Technology Co., Ltd.