

SMART SODIUM-ION BATTERY SERIES-4U

COSPOWERS

CN4875T

Application Field:
Communication base stations, macro station retrofits, power supply for shelters/outdoor cabinets, grid peak shaving and valley filling, and other scenarios, compatible with various energy storage system requirements.



Excellent high and low temperature performance

Operates with natural cooling at ambient temperatures below 50°C, saving energy.



Intelligent protection

Features smart voltage, current, and temperature protection functions.



Easy maintenance

Integrated BMS design supports battery self-management, remaining energy, battery health monitoring, and other functions.



Anti-theft functionality

Compatible with various optional anti-theft features.



Operating modes

Includes self-managed constant voltage discharge, power-managed constant voltage discharge, and battery-characteristic discharge modes such as constant power discharge, enabling hybrid use of different battery types.

BMS Introduction

	Introduction
Communication interface	RS485/RS232/CAN
Information sampling function	With each series-connected single cell voltage, external busbar voltage, total battery pack voltage, charging and discharging current, cell surface temperature, BMS single-board temperature sampling function
Battery Cell equalization function	The battery has a passive equalization function, which can be activated when the cell pressure difference exceeds a certain value during charging.
Charging current Limit function	With the function of automatically entering the current-limiting charging mode when detecting the battery cell: low voltage, high voltage, low temperature, high temperature, poor consistency, charging over-current protection
Voltage acquisition accuracy	0~5V, Detection accuracy≤10mV; 0~60V Detection accuracy≤0.5%
Current acquisition accuracy	Detection accuracy≤1% (0.5C charging/discharging)
Anti-theft function	Software anti-theft, communication anti-theft, gyroscope anti-theft and other functions
System component failure alarm	It has failure detection and alarm function for key components of BMS board. While it is detected with temperature sensor failure, voltage detection failures, charge and discharge MOS failure, an alarm will be generated and the charge and discharge loops will be disconnected (if the charge and discharge loop is damaged, it is not required to disconnect), the battery cannot recover automatically, and all the indicators flash to prompt.
History logs	500 historical records, 10000 historical records and life-cycle storage are optional; Independent storage space; BMS has power failure preservation capability; Historical data records include battery voltage, current, ambient temperature, SOC, SOH, cycle times, cumulative discharge capacity and other data

Module Specification and Parameters

Model	CN4875T
Connection Method	1P15S
Rated Energy	3480Wh
Rated Capacity	75Ah
Rated Voltage	46.4V
Voltage Range	40~58V(22~58V)
Charging Current	35A
Discharging Current	75A
Operating Temperature	Charging: -10~50°C; Discharging: -30~70°C; Storage: -30~45°C
Self-Discharge Rate	≤3% (0~30°C / 3 months)
Dimensions (W*D*H)	440*430*176mm
Weight	55Kg
Lifespan	4000 cycles @80% DOD, 0.5C/0.5C
Certification	YD2344.1-2023、UN38.3



Shenzhen Coslight Power Technology Co., Ltd.

W: WWW.COSPOWERS.COM

A: No.2, Guangtian Road, No.3 Industrial Zone, Luotian Community, Yanluo Street, Baoan District, Shenzhen, Guangdong Province, P.R.C

T: +86-755-33185898

Copyright and final interpretation rights belong to Shenzhen Coslight Power Technology Co., Ltd.