

PowerEco-125kW/261kWh

Products Compliant with Chinese Standards

Application Field:
Commercial Buildings, Industrial Parks,
Industrial Zones



Flexible Expansion, Multi-functional
in One Unit, Adaptable to Various
Application Scenarios



Multiple Protection
Systems



Highly Integrated Design
with AC/DC Integration



Touchscreen Monitoring
and Cloud-Based
Maintenance

Parameters/ Model		PowerEco-125kW/261kWh
DC Side Parameters	DC Bus Maximum Voltage	950V
	DC Side Maximum Current	203A
	DC Voltage Operating Range	650~950V
AC Grid-tied Parameters	Maximum Input Apparent Power	138kVA
	Maximum Input Active Power	125kW
	Rated Input Voltage	400Vac, 3P3W+PE/3P4W+PE
	Maximum Continuous Input Current	200A
	Rated Input Frequency	50/60Hz
AC Off-grid Parameters	AC Off-grid Voltage	400Vac, 3P3W+PE/3P4W+PE
	Maximum Continuous Output Current	200A
	AC Off-grid Frequency	50/60Hz
Battery Parameters	Cell Capacity	314Ah-LFP
	Rated Energy	261kWh
	Nominal Voltage	832V
	Operating Voltage Range	728~910V
	C-rate	≤0.5C
System level Parameters	HMI	7-inch LCD Touch Screen
	Fire Protection System	Perfluorohexanone Fire Extinguishing / Aerosol Fire Extinguishing
	Cooling Method	Liquid Cooling
	Operating Temperature	-20~55°C
	Protection Level	IP54
	Dimensions (W*D*H)	<1100*1350*2350mm
	Weight	<2900Kg
Other Parameters	Certifications	Cell:IEC62619,UL1973,UL9540A,UN38.3,RoHS,MSDS,Pack:UL9540A,UN38.3



Cospowers Technology Co., Ltd.
W: WWW.COSPOWERS.COM
A: No.28, Dongqi Road, Dongying City, Shandong Province, P.R.C.
T: +86-546-7768891
Copyright and final interpretation rights belong to Cospowers Technology Co., Ltd.