

CF48100T / CF48150T NEW

Application Fields:
Urban base stations,
remote area base
stations, emergency
communication base
stations, mobile base
stations, critical industry
base stations, high-load
base stations, and newly
constructed base
stations.



Excellent high and low temperature performance
Operates with natural cooling at ambient temperatures below 38°C, saving energy.



Intelligent protection
Equipped with intelligent voltage, current, and temperature protection functions.



Long service life
3000 cycles @ 0.5C, 80% DOD, at 25°C.



Easy maintenance
Integrated BMS design, supports battery self-management, remaining energy, battery health management, and other functions.



Anti-theft functionality
Compatible with various optional anti-theft features.

Parameters/Model	CF48100T		CF48150T	
Connection Method	1P15S	1P16S	1P15S	1P16S
Rated Energy	4800Wh	5120Wh	7200Wh	7680Wh
Rated Capacity	100Ah	100Ah	150Ah	150Ah
Rated Voltage	48V	51.2V	48V	48V
Voltage Range	42~52.5V	43.2~56.8V	42~52.5V	43.2~56.8V
Charging Current	50A	50A	75A	75A
Discharging Current	100A	100A	150A	150A
Operating Temperature	Charging: 0~50°C; Discharging: -20~55°C; Storage: -30~45°C			
Self-Discharge Rate	≤3% (at 0~30°C for 3 months)			
Dimensions (W*D*H)	440*420*130mm		440*525*130mm	440*525*130mm
Weight	41Kg	43Kg	56Kg	60Kg
Communication Interface	RS485/RS232/CAN			
Charging Current Limiting Function	Automatically activates current-limited charging when detecting cell conditions such as low voltage, high voltage, low temperature, high temperature, poor consistency, or overcurrent protection during charging.			
Voltage Measurement Accuracy	0~5V measurement range with accuracy ≤10mV; 0~60V measurement range with accuracy ≤0.5%			
Current Measurement Accuracy	Measurement accuracy ≤1% (at 0.5C charge/discharge)			
Anti-Theft Function	May support software-based anti-theft, communication-based anti-theft, gyroscope-based anti-theft, and other functionalities.			
Certifications	IEC62619、IEC62620、UL1973、UL9540A、UN38.3、ROHS、TLC、EMC		IEC62619、IEC62620、UL1973、UN38.3、ROHS、EMC	



Shenzhen Coslight Power Technology Co., Ltd.
W: WWW.COSPOWERS.COM
A: No.2, Guangtian Road, No.3 Industrial Zone, Luotian Community, Yanluo Street, Baoan District, Shenzhen, Guangdong Province, P.R.C
T: +86-755-33185898
Copyright and final interpretation rights belong to Shenzhen Coslight Power Technology Co., Ltd.